Precision Steel

precidur[®] 48CrMoNiV4-4

Product information for hot-rolled precision strip made in Hohenlimburg



Version 9/21

Tool steel

Hardenable tool steels from BU Precision Steel are used in roller and ball bearings and a wide variety of saw and blade applications such as circular saw blades, cutting knives, paper cutters and die plates.

The special advantages of the hot-rolled precision strip lie in its uniform properties and defined microstructure combined with optimum cleanness.

Close analysis ranges tailored to specific purposes and precisely controlled rolling parameters guarantee consistent and outstanding processability and optimum heat treatment results, yielding maximum wear resistance.

precidur®

- is used in virtually all industry sectors.
- offers close thickness tolerances similar to cold-rolled strip, optimum surface finishes and consistent material properties over the entire strip length and width.
- is characterized by its symmetrical strip profiles and mill edges.
- is the sum of all the experience we have gained in more than 100 years of manufacturing and processing steel.

Contents

Brief portrait Technical features Chemical composition Mechanical properties General thickness tolerances Delivery options

Technical features

Tool steel	
Material number:	Special mill grade
Proprietary brand:	precidur [®] 48CrMoNiV4-4
Application:	Tool steel for various applications

Chemische Zusammensetzung										
Ladle analysis mass percentages	C [%]	Si [%]	Mn [%]	P [%]	S [%]	Cr [%]	AI [%]	V [%]	Ni [%]	Mo [%]
min.	0.40	-	0.70	-	-	0.85	0.015	-	0.30	0.85
max.	0.50	0.30	1.00	0.025	0.015	1.20	0.100	0.20	0.70	1.20

Further special analyses available

Possible delivery options								
Options	Mill edge (NK) Cut edge (GK)	pickled	unpickled	slit	trimmed	Cut to length	annealed	not annealed
precidur [®] 48CrMoNiV4-4	NK or GK	🗸 or	✓	1	✓	✓	✓	✓

General thickness tolerances								
Strip thickness [mm]	1.5 – 2.54	2.55 – 4.03	4.04 - 6.03	6.04 - 8.03	8.04 - 9.03	9.04 - 11.03	11.04 - 14.03	14.04 - 16.00
Standard tolerances [mm]	± 0.04	± 0.04	± 0.05	± 0.055	± 0.06	± 0.07	± 0.08	± 0.10
Special tolerances [mm]	± 0.03	± 0.035	± 0.04	± 0.045	± 0.05	± 0.055	± 0.06	± 0.07

General delivery options			
Coil inner diameter:	standard 508 mm / optional 610 mm		
Coil outer diameter:	max. 1,890 mm		
Coil weight:	max. 20.5 kg/mm strip width		
Strip width*:	max. 720 mm		
Strip thickness*:	1.5 – 16 mm		

* May be subjected to restrictions.